

PS Mouldings Technical Specifications

TECHNICAL CHARACTERISTICS

IDENTIFICATION AND CLASSIFICATION	SYMBOL	SPECIFICATION
Product type		Polystyrene-based skirting board.
DIMENSIONAL CHARACTERISTICS	SYMBOL	SPECIFICATION
Element thickness		12 / 15 mm
Length		2250 mm
Width		80 / 100 mm
PRODUCT CHARACTERISTICS	SYMBOL	SPECIFICATION
Dimensional stability		High dimensional stability under indoor conditions.
Flatness		Concave–convex ≤ 0.5 mm
Gloss (60° angle)		30 - 35 gloss.
Stain resistance (10-minute exposure)		Tea / Coffee / Vinegar: no staining.
Coating adhesion		Resistant to the removal of masking tape adhered to the interior surface of the piece (temperature range: 5–30°C).
Water resistance		100% waterproof. After 48 hours in contact with water, it remains unaffected.
Water absorption		Waterproof.
Insect resistance		100%

ENVIRONMENTAL INFORMATION

ENVIRONMENTAL PROPERTIES		SPECIFICATION
Material identification		EPS (expanded polystyrene).
Recyclability		100% recyclable.
Recycled content		Up to 86,99%

FINAL DECLARATION

To cut the skirting boards, use a hand saw or a power saw fitted with a fine-tooth blade.
When using a power tool, prevent the blade from overheating, as this may affect the appearance of the finish.

Before using products containing solvents, alcohol or acetone, test them on an inconspicuous area, as they may cause surface deterioration and loss of gloss.

The declared performance values have been determined in accordance with the standards specified above.
For installation and maintenance conditions, please refer to the manufacturer's current technical instructions.